



SMQ7J Quad Rear Vision System

No blind Spot as with 360 view systems.

7-inch Quad Digital Screen with ultra-clear image. View 4 cameras at once or any combination. For example, all four sides and the system will trigger to one screen when turn signal or reverse is activated.

MONITOR SPECIFICATIONS

Screen size: 7-inch digital screen (16:9)

Built in Quad Multiplexer

Long Life Resolution: 800 x 480 Pixel (RGB)

System: PAL/NTSC selectable

Contrast: 500:1

Brightness: 450 cd/m2

Power supply: DC 12V~24V with reverse polarity protection

Operation temperatures: -30°~70°C

Storage temperature: -40°~80°C

4 AV color coded inputs with color coded trigger wires, auto blue screen if no signal on activated channel

Features: HD sunshade, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons & remote: image delay on time 0~10s, (for side cameras) Mirror/Normal image, multi-language featuring adjustable guidelines.



CAMERA SPECIFICATIONS C001J

Horizontal Resolution: 600 TV Lines

TV System: NTSC

Image Type: 1/3 Inch Color CCD Sharp® or equivalent –
(no cheap off brands used)

Effective pixel: 510 x 492

Illumination: 0 Lux (built-in 20 high output IR LEDs for night vision)

Aluminum housing

Waterproof: IP69K

Power supply: DC 12V (from monitor)

Shockproof: 10G

Operating temperature: -40°~70°C

Built-in microphone

Viewing angle: 120°



Optional ADD100Z

Aluminum Camera Cover
Available for J-series Camera

574-807-6002 www.verityrvs.com Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

A division of Component Solution Services, LLC.

Woman-Owned

Est. 2002

Subject to change without notice