## **VERITY REAR VISION SYSTEMS®**

## Just View It!®



Est. 2002

A Woman-Owned Company

Something new in Rear Vision! No blind Spot as with 360 view systems.

Our New Exclusive 7-inch Quad Digital Screen with ultra-clear image. View 4 cameras at once. For example, all four sides and the system will trigger to one screen when turn signal or reverse is activated.

## MONITOR SPECIFICATIONS

Screen size: 7-inch digital screen (16:9)

**Built in Quad Multiplexer** 

Long Life High Resolution: 800 x 480 Pixel (RGB)

System: PAL/NTSC selectable

Contrast: 400:1 Brightness: 450cd/m2

Power supply: DC 12V~24V with reverse polarity protection

Operation temperatures: -30~70°C Storage temperature: -40~80°C

4 AV color coded inputs with color coded trigger wires, auto blue screen if no signal on activated

channel

Features: HD sunshade, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons & remote: image delay on time 0~10s, (for side cameras) Mirror/Normal image, multi-language,

**NEW!** Adjustable guidelines.

## **CAMERA SPECIFICATIONS C001J**

**Horizontal Resolution: 700 TV Lines** 

TV System: NTSC

Image Type: 1/3 Inch Color CCD Sharp® or SONY®

(no cheap off brands used)

Effective pixel: NTSC:510(H)  $\times$  492(V)

Illumination: 0 Lux (built-in 20 high output IR LED's for night vision)

Aluminum housing. Waterproof: IP69K Power supply: 12V DC (from monitor)

Shockproof: 10G

Operating temperature: -40~70°C

Audio and IR night vision, Viewing angle: 120°



ADD100Z

Aluminum Camera Cover
Available for J-series Camera

& Fleets

574-807-6002 www.verityrvs.com Serving OEMs & Fleets
56600 Twin Branch Dr., Mishawaka, IN 46545
A division of Component Solution Services, LLC. Est. 2002