



# SM07J Rear Vision System

Our exclusive 7-inch digital screen with ultra-clear image in our custom housing. 32 Major improvements were made to this system. 20 years of installs, factory line audits, tech support calls, warranty calls, and a lifetime of "it would work better and longer if we could..." went into the development of this system.

## MONITOR SPECIFICATIONS (Part #MK05J)



- Screen size: 7-inch digital screen (16:9) (800x480 Pixel)
- Long Life High Resolution
- System: PAL/NTSC Auto Select
- Contrast: 450:1
- Brightness: 500 cd/m2
- Power supply: DC 12V~24V with reverse polarity protection
- Operation temperatures: -20°~70°C
- Storage temperature: -30°~80°C
- 61" monitor harness with waterproof fuse and color-coded trigger wires.
- Auto blue screen if no signal on activated channel.

Features: HD sunshade, auto light sensor dimming for buttons and LCD screen, LED blue light buttons, high quality processor, in-line waterproof fuse, easy to use OSD menu function via buttons & remote: reversing image delay time 0~10s, (for side cameras) Mirror/Normal image, plus horizontal flip per signal channel, multi-language, featuring adjustable guidelines.

## CAMERA SPECIFICATIONS (Part #C001J)

- Horizontal Resolution: 700 TV Lines
- TV System: NTSC
- Image Type: 1/3 Inch Color CCD Sharp® or equivalent
- Effective pixel: 510 x 492
- Illumination: 0 Lux (built-in 20 high output IR LEDs for night vision)
- Aluminum housing
- Waterproof: IP69K
- Power supply: DC 12V (from monitor)
- Shockproof: 10G
- Operating temperature: -40°~70°C
- Built-in microphone
- Viewing angle: 120°



Optional ADD100ZV  
Aluminum Camera Cover  
Available for J-series Camera

574-807-6002 [www.veritysafe.com](http://www.veritysafe.com) Serving OEMs & Fleets

56600 Twin Branch Dr., Mishawaka, IN 46545

Woman-Owned

A division of Component Solution Services, LLC.

Est. 2002

Subject to change without notice